
Keysight Technologies

U1240B Series Handheld Digital Multimeters



Data Sheet



Key Features

Check more, fix more

- 10,000-count display
- 0.09% basic DCV accuracy
- True RMS AC measurement
- Basic functions ACV, DCV, ACI, DCI, resistance, frequency, diode, continuity tests
- Advanced functions –
 Capacitance, temperature,
 MINMAX recording

Ease of use

- Adjustable backlighting two intensity levels
- Manual data logging (U1242B only)
- Built-in switch counter, harmonic ratio (U1242B only), dual/differential temperature capabilities (U1242B only)

Built to last

- Overmold body casing
- CAT III 1000 V and CAT IV 600 V safety protection
- Certified to CE and CSA standards
- Operating temperature-10 to 55 °C

Keysight Technologies, Inc. U1240B Series handheld digital multimeters enable you to check more with wider measurement ranges. They feature true RMS readings on their 10,000-count displays. The adjustable backlighting allows you to complete your jobs even in subdued lighting conditions, or to simply prolong battery life. Your maintenance tasks are greatly simplified due to the built-in switch counter, harmonic ratio, dual and differential temperature capabilities, with just a press of the button. The meters have a high safety rating with CAT III 1000 V and CAT IV 600 V protection and are certified to CE and CSA standards. On top of that, the U1240B Series comes with a certificate of calibration and test report – at no extra cost.

The latest multimeters in this series, the U1241B and U1242B, now come in vivid orange cases, offering the capabilities and functions you need.

Functions and ranges at a glance



DC specifications

Function	Range	Resolution	Test current/burden voltage	Accuracy ±(% of reading + counts of least significant digit) U1241B U1242B	
Voltage ¹	1000.0 mV	0.1 mV	-	0.09% + 5	
	10.000 V	0.001 V	-	0.09% + 2	
	100.00 V	0.01 V	-	0.0970 + 2	
	1000.0 V	0.1 V	-	0.15% + 5	
Current	1000.0 μΑ	0.1 μΑ	< 0.06 V (50 Ω)	0.1% + 3	
	10000 μΑ	1 μΑ	< 0.55 V (50 Ω)	0.1% + 3	
	100.00 mA	0.01 mA	< 0.18 V (0.5 Ω)	0.2% + 3	
	440.0 mA ²	0.1 mA	< 0.8 V (0.5 Ω)	0.5% + 3	
	10.000 A ³	0.001 A	< 0.4 V (0.01 Ω)	0.6% + 5	
Resistance ⁴	1000.0 Ω5	0.1 Ω	0.5 mA		
	10.000 kΩ ⁵	0.001 kΩ	50 μΑ	0.207 . 2	
	100.00 kΩ	0.01 kΩ	4.91 μΑ	0.3% + 3	
	1000.0 kΩ	0.1 kΩ	447 nA	_	
	10.000 ΜΩ	0.001 ΜΩ	112 nA	0.8% + 3	
	100.00 MΩ ⁶	0.01 ΜΩ	112 nA	1.5% + 3	
Diode test ⁷	1 V	0.001 V	approximately 0.5 mA	0.3% + 2	

- 1. Input impedance: $10 \text{ M}\Omega$ (nominal).
- 2. Current can be measured up to 440 mA continuously. An additional 0.2% needs to be added to the specified accuracy if the signal measured is in the range of 440 mA to 1100 mA for 30 seconds maximum. After measuring a current of > 440 mA, leave the meter to cool down for twice the measuring time used before applying a low current measurement.
- 3. Current can be measured up to 10 A continuously with a maximum operating temperature of 50 °C. An additional 0.3% needs to be added to the specified accuracy if the signal measured is in the range of 10 A to 19.999 A for 15 seconds maximum. After measuring a current of > 10 A, leave the meter to cool down for 60 seconds before applying a low current measurement.
- 4. The maximum open voltage is < 2.8 V. For instant continuity, the built-in buzzer sounds when resistance is < 10.0 Ω .
- 5. The accuracy of 1 k Ω and 10 k Ω is specified after Null function, which is used to substrate the test lead resistance and the thermal effect.
- 6. For the range of 100 M Ω , the R.H. is specified for < 60%. The temperature coefficient will be 0.15 times of specified accuracy as > 50 M Ω .
- 7. Overload protection: 1000 V RMS for circuits < 0.3 A short circuit current. The built-in buzzer sounds when reading is approximately below 50 mV and audible single tone for normal forward biased diode or semiconductor junction as 0.3 V ≤ Reading ≤ 0.8 V.

AC specifications

Function	Range	Resolution	Test current/burden voltage	Accuracy ± (% of reading + counts of least significant digit)		
				40 to 500 Hz	500 Hz to 1 kHz	1 to 2 kHz
AC voltage ^{1, 5}	1000.0 mV	0.1 mV	-		2% + 5	-
True RMS	10.000 V	0.001 V	-	- - 1% + 5	1% + 5	2% + 5
	100.00 V	0.01 V	-	1% + 5		2% + 5
	1000.0 V	0.1 V	-			-
AC current ^{2,5} True RMS	1000.0 μΑ	0.1 μΑ	< 0.06 V (50 Ω)	-	1.5% + 5	
	10000 μΑ	1 μΑ	< 0.55 V (50 Ω)			
	100.00 mA	0.01 mA	< 0.18 V (0.5 Ω)	1% + 5		-
	440.0 mA ³	0.1 mA	< 0.8 V (0.5 Ω)	_		
	10.000 A ⁴	0.001 A	< 0.4 V (0.01 Ω)	_		

- 1. Input impedance: $10 \text{ M}\Omega$ (nominal) in parallel with < 100 pF, with overload protection of 1000 V RMS
- $2. \quad \text{Crest factor} \leq 3. \text{ For non-sinusoidal waveforms with crest factor up to 3, add } 2\% \text{ reading } + 2\% \text{ full scale typical.}$
- 3. Current can be measured from 50 mA to 440 mA continuously. An additional 0.2% needs to be added to the specified accuracy if the signal measured is in the range of 440 mA to 1100 mA for 30 seconds maximum. After measuring a current of > 440 mA, leave the meter to cool down for twice the measuring time used before application of low current measurement.
- 4. Current can be measured from 0.5 A up to 10 A continuously with a maximum operating temperature of 50 °C. An additional 0.3% needs to be added to the specified accuracy if the signal measured is in the range of 10 A to 19.999 A for 15 seconds maximum. After measuring a current of >10 A, leave the meter to cool down for 60 seconds before applying a low current measurement.
- 5. AC voltage and AC current specifications are AC coupled. True RMS measurement is valid from 5 % of range to 100 % of range.

Temperature specifications

Thermocouple type	Range	Resolution	Accuracy ± (% of reading + offset error)
K (for U1241B and U1242B)	-40 to 1000 °C/-48 to 1832 °F	0.1 °C /0.1 °F	1% + 1 °C/1% + 1.8 °F
J (for U1242B only)	-40 to 1000 °C/-48 to 1832 °F	0.1 °C/0.1 °F	1% + 1 °C/1% + 1.8 °F

Capacitance specifications

Range	Resolution	Accuracy ± (% of reading + counts of least significant digit)
1000.0 nF	0.1 nF	
10.000 μF	0.001 μF	1.2% + 4
100.00 μF	0.01 μF	
1000.0 μF	0.1 μF	2% + 4
10.000 mF	0.001 mF	

Harmonic ratio specifications

Range	Frequency	Voltage
0.0% to 99.9%	40 to 500 Hz	100 mVAC to 1000 VAC

Switch counter definition

Switch condition ^{1, 2}	Circuit switch	Display ³	Switch threshold
Low level	Normally close	Lo	< 370 ohms
Intermittent ⁴	Close to open	Number of switch count	Low to high transition
High level	Normally open	Hi	> 430 ohms
Intermittent ⁵	Open to close	Number of switch count	High to low transition

- Detects intermittent Opens or Closes lasting for at least 250 µsec.
 Test current of 0.5 mA with maximum open circuit voltage of 0.000
- 2. Test current of 0.5 mA with maximum open circuit voltage of 2.8 V is used.

 3. Maximum count reading: 199.99 M (display "OL" when achieving 2 x 10⁸ and thereafter).

 4. Count only low to high transition for initial switch condition of Low.
- 5. Count only high to low transition for initial switch condition of High.

Frequency specifications

Range	Resolution	Accuracy	Minimum input frequency
100.00 Hz	0.01 Hz		
1000.0 Hz	0.1 Hz	_	
10.000 kHz	0.001 kHz	0.03%+3	1 Hz
100.00 kHz	0.01 kHz	_	
1000.0 kHz ¹	0.1 kHz	_	

^{1.} Effective frequency measurement of up to 200 kHz; refer to frequency sensitivity table below for details.

Frequency sensitivity during voltage measurement

Input range (Maximum input for specified accuracy = 10 x Range or 1000 V)	Minimum sensitivity (RMS sine wave)		
	20 Hz to 50 kHz	50 to 200 kHz	
1000.0 mV	0.3 V	0.6 V	
10.000 V	0.5 V	1.8 V	
100.00 V	5 V	10 V (< 100 kHz)	
1000.0 V	50 V	100 V (< 100 kHz)	

Frequency sensitivity during current measurement

Input range	Minimum sensitivity (RMS sine wave)
	20 Hz to 20 kHz
1000.0 μΑ	100 μΑ
10000 μΑ	500 μΑ
100.00 mA	10 mA
440.00 mA	50 mA
10.000 A	1 A

Measuring rate

Function	Times/second
ACV	7
DCV (V or mV)	7
Ω	14
Diode	14
Capacitance	4 (< 100 μF)
DCA (μA, mA, A)	7
DCA (μA, mA, A) ACA (μA, mA, A)	7
Temperature	7 (single)
Frequency	1 (> 10 Hz)

General Specifications

Display	Dual display (secondary display is intended for temperature function display only) consists of 4-digit liquid crystal display (LCD) with maximum reading of 11,000 counts. Automatic polarity indication.	
Power consumption	0.22 VA maximum	
Battery type and life	Four single standard 1.5 V AAA batteries (Alkaline or Zinc Chloride type); 300 hours typical	
Operating environment	Full accuracy at -10 to 55 °C; and to 80% RH for temperatures up to 30 °C, decreasing linearly to 50% RH at 55 °C 0 - 2000 meters per IEC 61010-1 3 rd edition CAT III, 1000 V/CAT IV, 600 V IEC 61010-1 3 rd edition	
Storage compliance	-20 to 70 °C	
Safety compliance IEC 61010-1:2010 / EN 61010-1:2010, IEC 61010-2-033:2012 / EN 61010-2-033:2012 Canada: CAN/CSA-C22.2 No.61010-1-12, CAN/CSA-C22.2 No. 61010-2-033-12 USA: ANSI/UL Std. No. 61010-1 (3rd Edition), ANSI/UL Std. No. 61010-2-033 (1st Edition)		
Measurement category	CAT III 1000 V/CAT IV 600 V Overvoltage Protection, Pollution Degree 2	
EMC compliance	Commercial limits compliance with EN61326-1 Influence of radiated immunity: In RF electromagnetic fields of 3 V/M	
	DC voltage measurement typical accuracy: 1000 mV to 1000 V range; ± 0.2% of range	
	DC current measurement typical accuracy: 1000 uA & 10000uA range; ± 0.7% of range 100 mA range; ± 0.22% of range 440 mA range; ± 0.5% of range 10 A range; ± 0.11% of range	
	Note: - If used in close proximity to an RF transmitter or when subjected to continuously present electromagnetic phenomena, some recoverable degradation of performance may occur.	
Common Mode Rejection Ratio (CMRR)	> 90 dB at DC, 50/60 Hz \pm 0.1% (1 k Ω unbalanced)	
Normal Mode Rejection Ration (NMRR)	> 60 dB at 50/60 Hz ± 0.1%	
Crest factor	< 3.0	
Temperature coefficient	0.1 × (specified accuracy)/°C (from -10 to 18 °C or 28 to 55 °C)	
Shock and vibration	Tested to IEC/EN 60068-2	
Dimensions (H x W x D)	193.8 x 92.2 x 58.0 mm	
Weight	450 g with batteries 400 g without batteries	
Warranty	Three years for main unit Three months for standard shipped accessories	

Ordering Information

Standard shipped accessories

Four 1.5 V AAA alkaline batteries Certificate of Calibration (CoC) Test probe leads (4-mm tips) Quick Start Guide Free test data (Option UK6)





U1241B

U1242

Optional accessories

Measuring accessories (non-temperature)

U1161A Extended test lead kit



Includes two test leads (red and black), two test probes, medium-sized alligator clips and 4-mm banana plugs.

- Test leads: CAT III 1000 V, CAT IV 600 V, 15 A
- Test probes: CAT III 1000 V, CAT IV 600 V, 15 A
- Medium-sized alligator clips: CAT III 1000 V, CAT IV 600 V, 15 A
- 4-mm banana plugs: CAT II 600 V, 10 A

U1162A Alligator clips



- One pair of insulated alligator clips (red and black). Recommended for use with Keysight standard test leads.
- Rated CAT III 1000 V, CAT IV 600 V, 15 A

U1163A SMT grabbers



- One pair of SMT grabbers (red and black). Recommended for use with Keysight standard test leads.
- Rated CAT II 300 V, 3 A

U1164A

Fine-tip test probes



- One pair of fine-tip test probes (red and black). Recommended for use with Keysight standard test leads.
- Rated CAT II 300 V, 3 A

U1168A

Standard test lead kit



Includes two test leads (red and black), 19-mm and 4-mm test probes, alligator clips, fine-tip test probes, SMT grabbers and mini grabber (black).

- Test leads: CAT III 1000 V, CAT IV 600 V, 15 A
- Test probes (19-mm tip): CAT II 1000 V, 15 A
- Test probes (4-mm tip): CAT III 1000 V, CAT IV 600 V, 15 A

(highly recommended for CAT IV environment)

- Alligator clips: CAT III 1000 V, CAT IV 600 V, 15 A
- Fine-tip test probes: CAT II 300 V, 3 A
- SMT grabber: CAT II 300 V, 3 A
- Mini grabber: CAT II 300 V, 3 A

U1169A

Test probe leads



Includes two test leads (red and black), and a pair each of 19-mm and 4-mm test probes.

- Test leads: CAT III 1000 V, CAT IV 600 V, 15 A
- Test probes (19-mm tip): CAT II 1000 V, 15 A
- Test probes (4-mm tip): CAT III 1000 V, CAT IV 600 V, 15 A (highly recommended for CAT IV environment)

U1583B AC current clamp



- Dual range: 40 A and 400 A
- Rated CAT III 600 V
- BNC-to-banana-plug adapter provided for use with DMMs


Ordering Information

Optional accessories Measuring accessories (temperature) U1180A Includes thermocouple adapter, thermocouple bead J-type and Thermocouple adapter+lead kit, thermocouple bead K-type. J and K types - T/C adapter J/K-type - T/C bead J-type: -20 to 200 °C - T/C bead K-type: -20 to 200 °C U1181A - Type-K T/C for use in oil and other liquids Immersion temperature probe - Measurement range: -50 to 700 °C - Includes adapter U1184A for connection to DMM U1182A - Type-K T/C for use on still surfaces Industrial surface temperature - Measurement range: -50 to 400 °C probe - Includes adapter U1184A for connection to DMM U1183A - Type-K T/C for use in air and non-caustic gas Air temperature probe - Measurement range: -50 to 800 °C - Includes adapter U1184A for connection to DMM U1184A - Mini-connector-to-banana-plug adapter for use with DMM Temperature probe adapter U1185A - T/C adapter J/K-type - T/C bead J-type: -20 to 200 °C J-type thermocouple and adapter U1186A - T/C adapter J/K-type K-type thermocouple and adapter - T/C bead J-type: -20 to 200 °C Carrying case U1172A The robust casing to transport your DMM and accessories Transit case (aluminium-clad) - Aluminum-clad, black panel construction - Dimension: 18 inches (H) x 13 inches (W) x 6 inches (D) - Weight: 4 kg U1174A The convenient way to carry your DMM and essential accessories Soft carrying case - Dimension: 9 inches (H) x 5 inches (W) x 3 inches (D) Hanging kit U1171A For fastening the DMM to a steel surface so both hands are free Magnetic hanging kit U1179A Connect with U1177A IR-to-Bluetooth adapter or U1173A IR-USB cable IR Connectivity Bracket

Evolving Since 1939

Our unique combination of hardware, software, services, and people can help you reach your next breakthrough. We are unlocking the future of technology. From Hewlett-Packard to Agilent to Keysight.







myKeysight

myKeysight

www.keysight.com/find/mykeysight

A personalized view into the information most relevant to you.

http://www.keysight.com/find/emt_product_registration

Register your products to get up-to-date product information and find warranty information.

KEYSIGHT SERVICES Accelerate Technology Adoption. Lower costs.

Keysight Services

www.keysight.com/find/service

Keysight Services can help from acquisition to renewal across your instrument's lifecycle. Our comprehensive service offerings—onestop calibration, repair, asset management, technology refresh, consulting, training and more—helps you improve product quality and lower costs.



Keysight Assurance Plans

www.keysight.com/find/AssurancePlans

Up to ten years of protection and no budgetary surprises to ensure your instruments are operating to specification, so you can rely on accurate measurements.

Keysight Channel Partners

www.keysight.com/find/channelpartners

Get the best of both worlds: Keysight's measurement expertise and product breadth, combined with channel partner convenience.

www.keysight.com/find/handhelddmm

For more information on Keysight Technologies' products, applications or services, please contact your local Keysight office. The complete list is available at: www.keysight.com/find/contactus

Americas

Canada (877) 894 4414 Brazil 55 11 3351 7010 Mexico 001 800 254 2440 United States (800) 829 4444

Asia Pacific

Australia 1 800 629 485 China 800 810 0189 800 938 693 Hong Kong 1 800 11 2626 India Japan 0120 (421) 345 080 769 0800 Korea Malaysia 1 800 888 848 Singapore 1 800 375 8100 0800 047 866 Taiwan Other AP Countries (65) 6375 8100

Europe & Middle East

For other unlisted countries: www.keysight.com/find/contactus (BP-9-7-17)

0800 0260637



United Kingdom

www.keysight.com/go/quality

Keysight Technologies, Inc. DEKRA Certified ISO 9001:2015 Quality Management System

